

KUBOTA B3150 HST NEILO BROOM COMBO



The legendary B Series Kubota & *nello* broom combo is compact enough to transport on a trailer yet rugged & powerful enough for the most demanding sealing contracts.



Over 150 Neilo Broom Combos in service in New Zealand Australia & South Pacific

Protect your operators from the dust and the harsh weather with the 31HP Kubota B3150HST Tractor & *nEIIO* broom combo with air Conditioned factory cabin.

The B3150 Broom Combo features a powerful Kubota 4 cylinder diesel engine, 3 range HST Hydrostatic transmission, and clutch-less hydraulic independent PTO to engage the broom pump.

We have combined the proven performance and reliability of the Kubota B Series with our unique broom technology to create the ultimate in compact easily transportable sweepers.

The B3150 Cabin Combo can be safely transported on a tandem trailer behind an average utility vehicle with a 2500kg tow rating

Our brooms spring loaded contour following lateral pivot substantially reduces brush wear and coning.

The *Kubota* Tractor & *neuo* Broom Combo is ready for work as soon as you receive it complete with Class one LED Beacon and remote mounted "Top Spin" pre cleaner. A custom trailer is also offered.



Kupota

FEATURE OVERVIEW

- 31hp engine with 3 range HST Hydrostatic transmission
- Air conditioned & heated factory cabin
- Remote mounted "Top Spin" pre cleaner
- Front mounted 1.75 m 5 section hydraulic driven broom
- Pivoting type hyd. lift, float & hydraulic left right angle
- Convenient joy stick to control broom lift, float and angle
- Broom drive via PTO driven hydraulic pump
- Clutchless engagement of broom drive
- Filtered rear mounted 60 litre hyd. res. for max. cooling
- Operator can easily replace brush sections in the field
- Unique spring activated contour following lateral pivot ensures even brush pressure & reduced coning



SPECIFICATION

Diesel Engine	V1505-E3-D26BH-A, 4 cylinder,1498cc
HP	31HP (22.8kw) @ 2500rpm
Transmission	3 range pedal operated HST (Hydrostatic) type
Fuel Capacity	27 litres
PTO	Clutchless hydraulic independent type
Air Filtration	Dual type filters with remote Donaldson "Top Spin" pre cleaner
Total tractor Hydraulic Flow	33.1 lpm (Broom hydraulic drive not included)
Steering	Hydrostatic power steering
Tyres Turf / Tarmac type	Front: 23x8.5 -12 rear: 13.6 -16 (Note: optional front industrial tyres available)
Broom Width Overall	2.130 metres
Sweeping Width (max)	1.750 metres
Sweeping Width (angle min)	1.660 metres
Broom Diameter	530mm
Number of Brush Sections	5 x 350mm
Broom Speed @ 540 @ PTO RPM	127 RPM
Angles left and Right	Variable to 60° left 60° right
Drive	Hydraulic Via a pump & 3.5 to 1 step up box on rear PTO
Broom Cooling/Oil Tank Capacity	60 litre tank with site glass mounted at rear of tractor
Contour Following Pivot	Unique Spring Loaded Contour Following Pivot
	Reduces brush wear and coning
Filtration/Breather	Return line filter / screw in breather on tank
Broom Lift, lower & float c/w safety lock	Joystick controlled SA valve (with key controlled electro/hyd. anti drop valve)
Electro Hyd. Anti Drop feature on broom	When key off anti drop valve will not allow broom to be lowered or creep
Broom Angle c/w safety lock	Joystick controlled DA valve (safety lock on joystick)
Length(L) Height (H) Cabin Combo	(L) With broom straight 3.990m (H)2.230m
Weight Tractor/ Broom	B3150 Cabin 1560 kg (with water in rear tyres)
Weight Tractor / Broom /Trailer Combo	B3150 Cabin 2240 kg (with water in rear tyres)
Replacement of Brushes	Remove two nuts. Pull off left hand end cap. Replace brush sections on shaft. Replace end cap and bolt.
Brush Manufacturer	NZ Brush Co. (recommended)
Country of Manufacture	Tractor Japan, Broom & Brush sections New Zealand
	וומטוט שאמוו, שוטטוו מ שוטאו זכטוטוא ועפע בכמומוע

Neil O'Fee Equipment reserves the right to change the above specification without notice We strongly recommend the use of seat belts in almost all applications.



Kubota Tractor Grader and Broom Combos distributed Australasia wide by NEIL O'FEE EQUIPMENT LTD Mobile 027 6642211 Office: (06) 3551139 Fax (06) 3551432 Email <u>neilofee.equipment@xtra.co.nz</u> Web site: <u>www.neilo.co.nz</u>

